

Type	Operating time for 90° in seconds		Torque range <sup>1)</sup>		Modulating torque <sup>2)</sup>	Number of starts	Valve attachment		Valve shaft			Handwheel		Weight <sup>3)</sup>
	50 Hz	60 Hz	Min. [Nm]	Max. [Nm]	Max. [Nm]	Max. c/h	Standard EN ISO 5211	Option EN ISO 5211	Cylindrical max. [mm]	Square max. [mm]	Two-flat max. [mm]	Ø mm	Turns for 90°	approx. [kg]
SQR 05.2	8	6	75	150	75	1,500	F05	F07	25.4	22	22	160	11	22
	11	9											16	
	16	12											11	
	22	17											16	
	32	25											11	
SQR 07.2	8	6	150	300	150	1,500	F07	F10	25.4	22	22	160	11	22
	11	9											16	
	16	12											11	
	22	17											16	
	32	25											11	
SQR 10.2	11	9	300	600	300	1,500	F10	F12	38	30	27	200	15	25
	16	12											11	
	22	17											15	
	32	25											11	
	45	35											15	
SQR 12.2	63	50	600	900	450	1,500	F12	F14	50	36	41	200	11	34
	16	12											22	
	22	17											30	
	32	25											22	
	45	35											30	
SQR 14.2	63	50	1,200	1,800	900	1,500	F14	F16	60	46	46	200	22	41
	36	30											51	
	48	40											70	
	72	60											51	
	100	85											70	

**General information**

Part-turn actuators AUMA NORM require external controls.

For sizes SQR 05.2 – SQR 14.2, AUMA offer AM or AC actuator controls. These can also easily be mounted to the actuator at a later date.

**Notes on table**

1) Torque range	The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
2) Modulating torque	Maximum torque for modulating duty
3) Weight	Indicated weight includes part-turn actuator AUMA NORM with 3-phase AC motor, standard electrical connection, unbored coupling and handwheel

**Features and functions**

Type of duty	Intermittent duty S4 - 25 %							
	For nominal voltage, 40 °C ambient temperature and at average load with 35 % of the max. torque							
Motors	3-ph AC asynchronous motor, type IM B9 according to IEC 60034							
Mains voltage, mains frequency	Standard voltages:							
	3-phase AC current - voltages/frequencies							
	Volt	380	400	415	440	460	480	500
	Hz	50	50	50	60	60	60	50
	Special voltages:							
	3-phase AC current - voltages/frequencies							
	Volt	525	575	660	690			
	Hz	50	50	50	50			
	Permissible variation of mains voltage: ±10 %							
	Permissible variation of mains frequency: ±5 %							
Overvoltage category	Category III according to IEC 60364-4-443							
Insulation class	Standard:		F, tropicalized					
	Option:		H, tropicalized					

Motor protection	Standard:	Thermoswitches (NC)
	Option:	PTC thermistors (according to DIN 44082) PTC thermistors additionally require a suitable tripping device in the controls.
Motor heater (option)	Voltages:	110 – 120 V AC, 220 – 240 V AC or 400 V AC (externally supplied)
	Power:	12.5 W:
Swing angle	Standard:	Adjustable between 75° and < 105°
	Options	15° to < 45°, 45° to < 75°, 105° to < 135°
Self-locking	Yes (Part-turn actuators are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.)	
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation	
	Options:	Handwheel lockable Handwheel stem extension
Indication for manual operation (option)	Indication whether manual operation is active/not active via single switch (1 change-over contact) For further information refer to separate data sheet Technical data for switches.	
Electrical connection	Standard:	AUMA plug/socket connector with screw-type connection
	Options:	Terminals or crimp connection Gold-plated control plug (sockets and plugs)
Threads for cable entries	Standard:	Metric threads
	Options:	Pg-threads, NPT-threads, G-threads
Terminal plan	TPA 00R1AA-101-000 (basic version)	
Splined coupling for connection to the valve shaft	Standard:	Coupling without bore
	Options:	Machined coupling with bore and keyway, square bore or bore with two-flats according to EN ISO 5211
Valve attachment	Dimensions according to EN ISO 5211 without spigot	

**Electromechanical control unit**

Limit switching	Counter gear mechanism for end positions OPEN and CLOSED	
	Standard:	Single switches (1 NC and 1 NO) for each end position, not galvanically isolated
	Options:	Tandem switches (2 NC and 2 NO) for each end position, switches galvanically isolated Triple switches (3 NC and 3 NO) for each end position, switches galvanically isolated Intermediate position switch (DUO limit switching), adjustable for any position
Torque switching	Torque switching adjustable for directions OPEN and CLOSE	
	Standard:	Single switches (1 NC and 1 NO) for each direction, not galvanically isolated
	Options:	Tandem switches (2 NC and 2 NO) for each direction, switches galvanically isolated
Position feedback signal, analogue (options)	Potentiometer or 0/4 – 20 mA (RWG)	
Mechanical position indicator	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED	
Running indication (option)	Blinker transmitter	
Heater in switch compartment	Standard:	Self-regulating PTC heater, 5 – 20 W, 110 – 250 V AC/DC
	Options:	24 – 48 V AC/DC or 380 – 400 V AC
	A resistance type heater of 5 W, 24 V AC is installed in the actuator in combination with the AM or AC actuator controls.	

**Electronic control unit (only in combination with AUMATIC AC actuator controls)**

Non-intrusive setting (option)	Magnetic limit and torque transmitter (MWG)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Mechanical position indicator	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED
Running indication	Blinking signal via controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC

Service conditions			
Use	Indoor and outdoor use permissible		
Mounting position	Any position		
Installation altitude	≤ 2,000 m above sea level for > 2,000 m above sea level, please contact AUMA		
Ambient temperature	Standard:	−40 °C to +60 °C	
	Options:	−60 °C to +60 °C	
Enclosure protection according to EN 60529	Standard:	IP 68 with AUMA 3-phase AC motor	
	Option:	DS Terminal compartment additionally sealed against interior (double sealed)	
	According to AUMA definition, enclosure protection IP 68 meets the following requirements:		
	<ul style="list-style-type: none"><li>• Depth of water: maximum 8 m head of water</li><li>• Duration of continuous immersion in water: Max. 96 hours</li><li>• Up to 10 operations during continuous immersion</li><li>• Modulating duty is not possible during continuous immersion.</li></ul>		
Pollution degree	Pollution degree 4 (when closed) according to EN 60664		
Vibration resistance according to IEC 60068-2-6	2 g, from 10 Hz to 200 Hz Resistant to vibration during start-up or for failures of the plant. However, a fatigue strength may not be derived from this. Valid part-turn actuators in version AUMA NORM (with AUMA plug/socket connector, without actuator controls).		
Corrosion protection	Standard:	KS	Suitable for installation in industrial units, in water or power plants with a low pollutant concentration as well as for installation in occasionally or permanently aggressive atmosphere with a moderate pollutant concentration (e.g. wastewater treatments plants, chemical industry)
	Options:	KX	Suitable for installation in extremely aggressive atmospheres with high humidity and high pollutant concentration
		KX-G	Same as KX, however aluminium-free version (outer parts)
Finish coating	Powder coating		
Colour	Standard:	AUMA silver-grey (similar to RAL 7037)	
	Option:	Other colours are possible on request.	
Lifetime	AUMA part-turn actuators meet or even exceed the lifetime requirements of EN 15714-2. Detailed information can be provided on request.		

Further information	
EU Directives	Electromagnetic Compatibility (EMC): (2004/108/EC) Low Voltage Directive: (2006/95/EC) Machinery Directive: (2006/42/EC)
Reference documents	Dimensions Part-turn actuators SQ 05.2 – SQ 14.2/SQR 05.2 – SQR 14.2 Electrical data Part-turn actuators SQR 05.2 – SQR 14.2 with 3-phase AC motors Technical data Electronic position transmitter/potentiometer Technical data for switches